

## TRICOTECH®

TRICOTECH® 12,5MM - CADMIUMFREE

**Thermoplastic water hose**  
with special constructed knitted insertions.

Marking: Tricotech® Dimension - cadmiumfree

Norm	EN ISO 1307:2008	Construction tube	Smooth
Working pressure at 20°C	10,0 bar	Color tube	Black
Bursting pressure	25 bar	Compound cover	PVC
Min. temperature	-10 °C	Cover	Smooth
Max. temperature	+60 °C	Color cover	Yellow
Compound tube	PVC	Reinforcements	Textile plies

Art.-no.	Ø Inner (mm)	Wall (mm)	Ø Outer (mm)	Bending radius (mm)	Weight (kg/mtr)	Length (mtr)
4100012000	12,5	2,25	17,0	125	0,160	25/50
4100015000	15,0	2,5	20,0	125	0,190	50
<b>4100019000</b>	<b>19,0</b>	<b>3,0</b>	<b>25,0</b>	<b>160</b>	<b>0,270</b>	<b>25/50</b>
4100025000	25,0	3,5	32,0	200	0,420	50
4100032000	32,0	5,0	42,0	300	0,760	50
4100040000	40,0	5,0	50,0	350	0,960	50
4100050000	50,0	6,0	62,0	400	1,420	25

**Application:** Smooth, flexible and torsion-free water hose that can be used as a water supply hose on construction sites, irrigation applications and is also frequently used as garden hose.

**Remark:**

- Cutted length not possible

**We recommend assembly with**

5310  
Geka® couplings



5354  
Geka® nozzle



6060  
ABA clamps

